PRODUCT GUIDE: NF0410-HB

INTEGRITY
LIGHTING SOLUTIONS

NF0410-HB | NEON FLEX | 10W/M | 24V | IP65 / IP67 |

Micro-profile horizontal-bend Neon Flex, 4 × 10mm

- 10W per metre output with a compact rectangular profile
- IP65 as standard; IP67 with injection-moulded end caps and input leads
- Supplied in lengths up to 5m
- Available in 2700K, 3000K, 4000K and 6000K
- >90 CRI
- 5 year warranty
- UKCA, UL and RoHS certified; tested to the international LM80 standard

IP67	5M MAX	2835 LED	5 YEAR WARRANTY	120° BEAM ANGLE	DIMMABLE
UKCA	UL	RoHS	41.6MM CUT	144 LEDS/M	LM80

www.integritylighting.co.uk | 0116 436 2450
15 Kernan Drive, Loughborough, England, LE11 5JF

TECH SPECS

PRODUCT SKU	NF0410-HB-24V-27K NF0410-HB-24V-3K NF0410-HB-24V-4K NF0410-HB-24V-6K
IP RATING	IP65; IP67 WITH MOULDED END CAPS
INPUT VOLTAGE	24V DC
WATTAGE	10W / M
WIDTH	4MM
HEIGHT	10MM
LUMEN 2700K	130LM / M
LUMEN 3000K	140LM / M
LUMEN 4000K	150LM / M
LUMEN 6000K	160LM / M
CRI	>90
LED CHIP SIZE	2835
LEDS PER METRE	144 LEDS/M
CUTTING INCREMENT	41.6MM
BEAM ANGLE	120°
OPERATING TEMPERATURE	-10° TO 45°C
DIMMABLE	YES, WITH COMPATIBLE LED DRIVER
LED LIFE (LM80)	50,000 HOURS
WARRANTY	5 YEARS